

Number Series **TPC600** A Class HDPE ADA Slotted **DG0675** Polycast 600 23 7/8" [606mm] 5 3/16" [132mm] Ø7/16 [11mm] THRU HOLE W/Ø13/16 [21mm] COUNTERSINK X 5/16 [8mm] DEEP 3/4" [19mm]

Manufacturer



Specification

POLYCAST DG0675 GRATE IS A HIGH DENSITY POLYETHYLENE ADA GRATE. WHEN USED IN HIGH VELOCITY TRANSVERSE SHEET FLOW APPLICATIONS, THE LONGITUDINAL SLOTS CREATE TURBULENCE TO IMPROVE ENTRY OF FLOW INTO THE CHANNEL. LOCKING DEVICE PART NO DA0642 SHOULD BE USED. THE GRATE HAS 23% (28 IN2) OF OPEN AREA. MEETS LOAD CLASS A.

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTIBILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.