Supplied By: 877-903-7246 19<mark>%</mark>16" [497mm] GRATE LENGTH www.trenchdrainsupply.com 47/8" [124mm] GRĂTE WIDTH 11/16" [27mm] SLOT LENGTH 1/4" [6mm] SLOT WIDTH **PLAN VIEW** 3/4" [19mm] GRATE HEIGHT **EDGE VIEW** 6<mark>/</mark>8" [155mm] ABTDRAIN® CHANNEL MONOLITHIC **EXPANSION JOINT CONCRETE POUR BOTH SIDES** (PREFERRED) (ACCEPTABLE) **CONCRETE THICKNESS** AND REINFORCEMENT PER LOCK DOWN BOLT STRUCTURAL ENGINEER'S SPECIFICATION FOR RED DOT® LOCK INSERT THE APPLICATION POLYLOCK™ **LOCK TOGGLE** FLOOR SLAB THICKNESS. **ANCHOR RIB** OR 4" [100mm], OR SPECIFICATION SOIL SUBGRADE (WHICHEVER IS GREATER) **CROSS SECTIONAL VIEW** GRAPHIC SCALE BAR SPECIFICATION DRAWING © 2005 ABT, Inc.



## INLAY ADA / HEEL PROOF THERMOPLASTIC GRATE

FILE: 2336-00 PART: 2336

Proprietary rights of ABT, Inc. are included in the information disclosed herein. The recipient, by accepting this document, agrees that neither this document nor the information disclosed herein nor any part thereof shall be copied, reproduced or transferred to others for manufacturing or for any other purpose except as specifically authorized in writing by ABT, Inc.

<u>DISCLAIMER</u>: The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from ABT, and EXCEPT AS EXPRESSLY PROVIDED IN ABT'S STANDARD WARRANTIES, ABT MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMER'S APPLICATION. Copies of ABT's standard warranties are available upon request.