


Type 405Q/406Q Mesh galvanized steel grate

Product Features

- Certified to EN 1433 Load Class C - 56,000 lbs - 1,162 psi
- Uses 'QuickLok' boltless locking system
- Suitable for use with K100, KS100, C100, H100-8, H100-10, and H100K-8 channels
- Manufactured from 13 gauge galvanized steel
- Complies with ADA - American Disabilities Act of 1990 Section 4.5.4
- Bicycle Tire Penetration Resistant to AS3996-2006



Specifications

General

The surface drainage system shall be ACO Drain K100, KS100, C100, H100-8, H100-10, and H100K-8 channels* complete with ACO Type 405Q/406Q Mesh galvanized steel grate with 'QuickLok' locking as manufactured by ACO Polymer Products, Inc. or similar approved.

Materials

The covers shall be manufactured from galvanized steel and have **minimum** properties as follows:

- **Independently certified to meet Load Class C to EN 1433 - 56,000 lbs - 1,162 psi**
- **13 gauge galvanized steel**
- **Intake area of 58.0 sq. in. (374.2 cm²) per half meter of grate**

The overall width of 4.84" (123mm) and overall length of 39.37" (1000mm) (Type 405) and 19.69" (500mm) (Type 406). Slots measure 1.20" (30mm) by 0.50" (13mm).

Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as appropriate



Supplied By:

TRENCHDRAIN
SUPPLY


877-903-7246

www.trenchdrainsupply.com

ACO Specification Information

ACO DRAIN**Type 405Q/406Q Mesh galvanized steel grate****Plan view****Side elevation**

Description	Part No.	Length inches (mm)	Width inches (mm)	Weight lbs.
QuickLok grates				
Type 405Q Mesh galvanized grate	98707	39.37 (1000)	4.84 (123)	7.8
Type 406Q Mesh galvanized grate	98714	19.69 (500)	4.84 (123)	3.9
QuickLok locking bar	02899	-	-	0.2
QuickLok grate removal hook	01318	-	-	0.6

'QuickLok' locking mechanism

ACO 'QuickLok' is a patented boltless locking system, grates are removed and replaced with the minimum time and effort for ease of maintenance. The unique design provides a positive 'snap down' fit into the locking bar. A stud is fixed to the grate which 'locks' into the spring clip in the locking bar.

The 'QuickLok' stud is made from stainless steel and high density nylon, the locking bar and clip are stainless steel, for use in both general purpose and corrosive environments.

ACO Polymer Products, Inc.**Northeast Sales Office**

P.O. Box 245
Chardon, OH 44024
Tel: (440) 285-7000
Toll free: (800) 543-4764
Fax: (440) 285-7005

West Sales Office

P.O. Box 12067
Casa Grande, AZ 85130
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-9899

Southeast Sales Office

4211 Pleasant Road
Fort Mill, SC 29708
Toll free: (800) 543-4764
Fax: (803) 802-1063

Follow us on**Electronic Contact:**

info@ACODrain.us
www.ACODrain.us

SPEC
INFO
ACO