Product Features

- Certified to EN 1433 Load Class C 56,000 lbs 1,162 psi
- Uses 'QuickLok' boltless locking system
- Suitable for use with K300, KS300, H300K-13, and H300KS-13 channels
- Manufactured from stainless steel Grade 304
- Bicycle Tire Penetration Resistant to AS 3996 2006



Specifications

General

The surface drainage system shall be ACO Drain K300, KS300, H300K-13, and H300KS-13, channels* complete with ACO Type 830Q mesh stainless steel grate with 'QuickLok' locking as manufactured by ACO Polymer Products, Inc. or similar approved.

Materials

The covers shall be manufactured from galvanized steel and have minimum properties as follows:

- Independently certified to meet Load Class C to EN 1433 - 56,000 lbs - 1,162 psi
- Grade 304 stainless steel
- Intake area of 192 sq. in. (1238.7 cm²) per half meter of grate

The overall width of 13.31" (338mm) and overall length of 39.37" (1000mm). Slots measure at a maximum of 1.46" (37mm).

Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as appropriate



Supplied By:



ACO DRAIN Type 830Q Mesh stainless steel grate

U Informatio Specification 00 V



Description	Part No.	Length inches (mm)	Width inches (mm)	Weight Ibs.
QuickLok grate Type 830Q Mesh stainless steel grate QuickLok locking bar QuickLok grate removal tool	16006 10458 01318	19.69 (<i>500</i>) - -	13.35 (<i>339</i>) - -	29.5 0.7 0.3



ACO Polymer Products, Inc.

Supplied By

877-903-7246

www.trenchdrainsupply.com

SUP

Northeast Sales Office P.O. Box 245 Chardon, OH 44024 Tel: (440) 285-7000 Toll free: (800) 543-4764

West Sales Office P.O. Box 12067 Casa Grande, AZ 85130 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899

Southeast Sales Office 4211 Pleasant Road Fort Mill, SC 29708 Toll free: (800) 543-4764 Fax: (803) 802-1063

Follow us on £ B Ξ

Electronic Contact: info@ACODrain.us www.ACODrain.us

C May 10, 2013 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products Inc. reserves the right to change the product and specifications without notice.

Fax: (440) 285-7005



M C 🖧