ACO DRAIN MiniKlassik galvanized steel perforated grate

Product Features

- Certified to EN 1433 Load Class A 3,500 lbs 91 psi
- Grates do not lock down
- Suitable for use with K50
- Manufactured from 14 gage galvanized steel
- Complies with ADA American Disabilities Act of 1990 Section 4.5.4
- Complies with ASME: A112.6.3 2001: Section 7.12
 Heel Resistant Strainers and Grates
- Bicycle Tire Penetration Resistant to AS3996-2006

Specifications

General

The surface drainage system shall be ACO Drain MiniKlassik K50 channels complete with ACO MiniKlassik galvanized steel perforated grate as manufactured by ACO Polymer Products, Inc. or similar approved.

Materials

The covers shall be manufactured from galvanized steel and have **minimum** properties as follows:

- Independently certified to meet Load Class A to EN 1433 - 3,500 lbs - 91 psi
- 14 gage galvanized steel
- Intake area of 14.5 sq. in. (93.5 cm²) per meter grate

The overall width of 2.95" (75mm) and overall length of 39.37" (1000mm). Perforations measure 0.23" (5.84mm) in diameter.

Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.





ACO DRAIN MiniKlassik galvanized steel perforated grate



Plan view 39.37" (1000mm) Account of the second se

Description	Part No.	Length inches (mm)	Width inches (mm)	Weight Ibs.
MiniKlassik Galvanized steel perforated grate	94699	39.37 (<i>1000</i>)	2.95 (<i>75</i>)	4.0

Supplied By:



www.trenchdrainsupply.com

ACO Polymer Products, Inc.

Northeast Sales Office P.O. Box 245 Chardon, OH 44024 Tel: (440) 285-7000 Toll free: (800) 543-4764 Fax: (440) 285-7005

Feb 13/1

West Sales Office P.O. Box 12067 Casa Grande, AZ 85130 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899 **Southeast Sales Office** 4211 Pleasant Road Fort Mill, SC 29708 Toll free: (800) 543-4764 Fax: (803) 802-1063



Electronic Contact: info@ACODrain.us www.ACODrain.us



