

1-877-903-7246



www.trenchdrainsupply.com

<p>Number</p> <p>100-DIL-C-DC</p>	<p>Series</p> <p>CPS100</p> <p>C Class DI Longitudinal Slotted Grate</p> <p>Pro Plus 100</p>
<div data-bbox="139 394 464 716"> </div> <div data-bbox="155 753 1524 1545"> <p>Top View Dimensions:</p> <ul style="list-style-type: none"> Overall Length: $19 \frac{9}{16}$ [497] Distance from End to Center Hole: $9 \frac{3}{4}$ [248] Distance between Locking Bar Holes: $3 \frac{3}{16}$ [81] Typical Hole Diameter: $\frac{5}{8}$ TYP [16] Overall Width: $4 \frac{13}{16}$ [122] Typical Slot Width: $\frac{3}{16}$ TYP [5] <p>Side View Dimensions:</p> <ul style="list-style-type: none"> Overall Height: $\frac{13}{16}$ [20] <p>End View Dimensions:</p> <ul style="list-style-type: none"> Overall Width: $\frac{13}{16}$ [20] <p>LOCKING BAR (ORDER SEPERATELY) 360141</p> </div>	
<p>Manufacturer</p>	<p>Specification</p> <p>JOSAM 100-DIL-C-DC EPOXY-COATED, DUCTILE IRON SLOTTED GRATE WITH CENTER HOLE FOR LOCKING BAR SECUREMENT. . MEETS CLASS C LOADING (56,000 LBS - 1,162 PSI). MEETS ADA AND HEELPROOF REQUIREMENTS, SUPPLIED BY TRENCH DRAIN SUPPLY.</p>
<p>DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.</p>	