

1-877-903-7246



www.trenchdrainsupply.com

<p>Number</p> <p>100-DIS-F-PS</p>	<p>Series</p> <p>CPS100</p> <p>F Class Ductile Iron Slotted Grate</p> <p>Pro Plus 100</p>
<div data-bbox="139 394 464 716"> </div> <div data-bbox="896 539 1359 667"> <p>NOTE: FREE AREA IS 28.6 SQ. IN. PER 1/2 METER GRATE</p> </div> <div data-bbox="133 783 1459 1577"> <p>Top View Dimensions:</p> <ul style="list-style-type: none"> Length: $19 \frac{5}{8}$ [498] Width: $4 \frac{3}{4}$ [122] Slot Width: $\frac{1}{2}$ TYP SLOT WIDTH [12] <p>Side View Dimensions:</p> <ul style="list-style-type: none"> Height: $\frac{3}{4}$ [20] <p>End View Dimensions:</p> <ul style="list-style-type: none"> Width: $1 \frac{1}{4}$ [32] </div>	
<p>Manufacturer</p>	<p>Specification</p> <p>JOSAM 100-DIS-F-PS EPOXY COATED, DUCTILE IRON SLOTTED GRATE WITH PRO-SNAP™ SECUREMENT. DESIGNED TO FIT PROPLUS 100 SIZE CHANNEL. MEETS CLASS F LOADING REQUIREMENTS. MEETS ADA SLOT REQUIREMENTS SUPPLIED BY TRENCH DRAIN SUPPLY.</p>
<p>DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.</p>	