


1-877-903-7246



www.trenchdrainsupply.com

Number 153585A	Series CPS300HD C Ductile Iron Slotted Half Meter Pro Plus 300
<div data-bbox="110 415 557 653"></div> <div data-bbox="792 392 1310 457"><p>Grate Modified for use with 300C-DI (152433P) Frame only. CPS300HD Series</p></div> <div data-bbox="722 558 1382 636"><p>NOTE: FREE AREA IS 127.0 SQ. IN. PER 1/2 METER SECTION</p></div> <div data-bbox="272 720 1294 1587"><p>Technical drawing showing dimensions for the grating:</p><ul style="list-style-type: none">Top view: Overall width 19.69, overall height 12.72, typical slot width 11.61 TYP, typical slot spacing .71 TYP.Side view: Slot depth 1.79, top flange thickness .79.End view: Overall width 12.60.Label: PROFIX SECURING FEATURE points to the top flange.</div>	
Manufacturer  Quality engineered trench drain system	Specification MEA-JOSAM 153585A DUCTILE IRON SLOTTED GRATING WITH PROFIX SECURING FEATURE. TWO TABS ARE REMOVED. DESIGNED TO FIT PRO-PLUS 300 SERIES CHANNEL WITH DUCTILE IRON FRAME. MEETS CLASS C LOADING REQUIREMENTS. (56,000 LBS - 1,162 PSI) SUPPLIED BY TRENCH DRAIN SUPPLY.
<p>DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.</p>	