


Location:



Polypropylene Longitudinal Slotted Grate to suit 4" clear opening channels



Specification: T100-PGA-HPP-BLK polypropylene longitudinal slotted grates are independently certified to meet Load Class A tested in accordance with EN1433 (3,372 lbs. {15 kN}). The grate length is 19.69" (.50 meter). The grate utilizes the patented "Clipfix" grate locking mechanism. The system (combined grate and channel) provides longitudinal shift protection.



CLIPFIX ADVANTAGE

The MEA polymer concrete and GRP channels are designed for our universal CLIPFIX grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.

LOAD CLASS A



EN 1433 -
3,372 LBS., 15kN,
70 PSI

Compliance



ADA



HEELPROOF

Supplied By:

 877-903-7246
 www.trenchdrainsupply.com

| GRATE MODEL NUMBER | LENGTH |
|--------------------|-----------------|
| T100-PGA-HPP-BLK | 19.69" (500 mm) |

| | |
|--------------------|--------------------------|
| Job Name: _____ | Page No: _____ |
| Section No: _____ | Contractor: _____ |
| Schedule No: _____ | Purchase Order No: _____ |

Revision Date: 2023-02-02

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

MIFAB reserves the right to make changes in material and design without formal notice and obligation. USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880