



Location:



Galvanized Steel Slotted Grate to suit 4" clear opening channels



Specification: T100-PGC-13-SD galvanized paverslot grates are independently certified to meet Load Class C tested in accordance with EN1433 (56,200 lbs. 250kN). The grate length is 39.37" (1 m). The grates utilize the patented "Clipfix" grate locking mechanism. The system (channel and grate) provides longitudinal shift protection. Optional (.5 m) grates are also available in Load Class C (Part # T100-PGC-13-SD-500).



CLIPFIX ADVANTAGE

The MEA polymer concrete and GRP channels are designed for our universal CLIPFIX grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.

LOAD CLASS C



EN 1433 - 56,200 LBS.,
250kN, 1,160 PSI

Compliance



ADA



HEELPROOF

GRATE MODEL NUMBER	LENGTH	USED WITH
T100-PGC-13-SD	39.37" (1000 mm)	T1500 Concrete Channel
T100-PGC-13-SD-500	19.69" (500 mm)	T1500 Concrete Channel
TP100-PGC-13-SD	39.37" (1000 mm)	T1400 Plastic Channel or T1330 Aluminum Channel
TP100-PGC-13-SD-500	19.69" (500 mm)	T1400 Plastic Channel or T1330 Aluminum Channel

Supplied By:



877-903-7246

www.trenchdrainsupply.com

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____