

T1700-PB-3 with Stainless Steel Integral Rail




Specification:

MIFAB®'s T1700-PB-3 series channels shall be 39.4" (1000 mm) long with a 8" (200 mm) internal width. Interconnecting channels sections are made from high strength Polymer Concrete and available in sloping and non-sloping (neutral) channels. Each channel comes with a standard stainless steel edge rail which is mechanically embedded in the channel.

Installation devices, plastic end cap/outlet cap, and catch basins are available accessories. System comes complete with 4" preformed bottom outlets at neutral locations. Grates (separate Specification Sheets) are available in in Load Class A-E in a variety of materials. Grates utilize the patented "Clipfix" locking mechanism.

CHANNEL MODEL#	BODY TYPE Sloped5% Neutral - 0%	ВС	ERT DDY PTH E2 (Max.)	OVER BOI DEP E1 (Min.)	ΟY	MAXIMUM FLOW RATE GPM	WEIGHT (LESS GRATE) LBS.
		, ,		, ,	, ,		
T1700N-PB-3	Neutral	7.29"	7.29"	9.06"	9.06"	416.86	63.21
T1700N-PB-3-B06	Neutral	7.29"	7.29"	9.06"	9.06"	416.86	63.21
T700N-PB-3-500	Neutral	7.29"	7.29"	9.06"	9.06"	416.86	32.36
T1701-PB-3	Sloped	7.29"	7.49"	9.06"	9.06"	396.26	63.34
T1702-PB-3	Sloped	7.49"	7.68"	9.26"	9.45"	396.26	64.04
T1703-PB-3	Sloped	7.68"	7.88"	9.45"	9.65"	396.26	64.74
T1704-PB-3	Sloped	7.88"	8.08"	9.65"	9.85"	396.26	65.44
T1705-PB-3	Sloped	8.08"	8.27"	9.85"	10.04"	396.26	66.13
T1706-PB-3	Sloped	8.27"	8.47"	10.04"	10.24"	396.26	66.83
T1707-PB-3	Sloped	8.47"	8.67"	10.24"	10.44"	396.26	67.53
T1708-PB-3	Sloped	8.67"	8.86"	10.44"	10.63"	396.26	68.23
T1709-PB-3	Sloped	8.86"	9.06"	10.63"	10.83"	396.26	68.93
T1710-PB-3	Sloped	9.06"	9.26"	10.83"	11.03"	396.26	70.33
T1710-PB-3-B06	Sloped	9.06"	9.26"	10.83"	11.03"	396.26	70.33
T1710N-PB-3	Neutral	9.26"	9.26"	11.03"	11.03"	576.95	70.77
T1710N-PB-3-B06	Neutral	9.26"	9.26"	11.03"	11.03"	576.95	71.87
T1710N-PB-3-500	Neutral	9.26"	9.26"	11.03"	11.03"	576.95	35.94
T1711-PB-3	Sloped	9.26"	9.45"	11.03"	11.23"	492.94	71.03
T1712-PB-3	Sloped	9.45"	9.65"	11.23"	11.42"	492.94	71.73
T1713-PB-3	Sloped	9.65"	9.85"	11.42"	11.62"	492.94	72.42
T1714-PB-3	Sloped	9.85"	10.04"	11.62"	11.82"	492.94	73.13
T1715-PB-3	Sloped	10.04"	10.24"	11.82"	12.01"	492.94	73.82
T1716-PB-3	Sloped	10.24"	10.44"	12.01"	12.21"	492.94	74.52
T1717-PB-3	Sloped	10.44"	10.63"	12.21"	12.41"	492.94	75.22
T1718-PB-3	Sloped	10.63"	10.83"	12.41"	12.60"	492.94	75.92
T1719-PB-3	Sloped	10.83"	11.03"	12.60"	12.80"	492.94	76.62
T1720-PB-3	Sloped	11.03"	11.23"	12.80"	13.00"	492.94	77.32
T1720-PB-3-BO6	Sloped	11.03"	11.23"	12.80"	13.00"	492.94	77.32
T1720N-PB-3	Neutral	11.23"	11.23"	13.00"	13.00"	708.51	79.87
T720N-PB-3-BO6	Neutral	11.23"	11.23"	13.00"	13.00"	708.51	79.81
T1720N-PB-3-500	Neutral	11.23"	11.23"	13.00"	13.00"	708.51	36.38



T1700-CB820-3 Stainless Steel Edge Catch Basin

Sediment bucket included

CATCH BASIN TOP ASSEMBLY CATCH BASIN OPTIONAL **EXTENSION** 8" OUTLET CATCH **BASIN BASE** (6" OUTLET ALSO AVAILABLE)

7.87
13.5"
7.67"
12"
13.5"
8.8
11.6" 7.9"





CLIPFIX ADVANTAGE

The MEA polymer concrete channels have been designed for our universal CLIPFIX grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.

Job Name:	Page No:
Section No:	Contractor:
Schedule No:	Purchase Order No:

Revision Date: 02/18/2022

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.