
877-903-7246 www.trenchdrainsupply.com

R-4972 Series

Concrete Floor Protector

Heavy Duty




R-4972-C



Cast iron grids provide a surface resistant to impact, abrasion and corrosion – afford better traction. Laid in areas subjected to heavy truck traffic, floor grids are invaluable in protecting the floor from excessive wear. Concrete is poured flush with the top of the casting so that the exposed iron protects the concrete. Grate is pushed into concrete as it is poured.


Dimensions in inches						
Catalog No.	Size	Thickness				
R-4972-C	24 x 24	7/8				
R-4972-D	18 x 36	7/8				




R-4976 to R-4977 Series

Areaway Grate

Light Duty







Type A with lip to set on top of areaway wall. Type B to set in recess of areaway wall.

For use over window wells providing maximum light transmission. Also suitable for use as ventilating and shaft gratings.

Dimensions in inches							
Catalog No.	Catalog No.						
Type A	Type B	Α	В	Openings	Bars		
	Half Round						
R-4976-1A	R-4976-1B	12 x 24	1	1 1/4	1/4		
R-4976-2A	R-4976-2B	15 x 30	1	1 1/4	1/2		
R-4976-3A	R-4976-3B	20 x 40	1 1/4	1 1/4	5/16		
R-4976-4A	R-4976-4B	24 x 48	1 1/4	1 1/4	5/16		
	Rectangular						
R-4977-1A	R-4977-1B	12 x 24	1	1 1/4	1/4		
R-4977-2A	R-4977-2B	15 x 30	1	1 1/4	1/4		
R-4977-3A	R-4977-3B	20 x 40	1 1/4	1 1/4	5/15		
R-4977-4A	R-4977-4B	24 x 48	1 1/4	1 1/4	5/16		
R-4977-5A	R-4977-5B	30 x 60	1 1/4	1 1/4	5/16		

Note: on Type A, grate size exceeds dimension "A" by 1-1/2" on all except wall side.

Note: on Type B, grate is 1" wider and 2" longer than dimension "A".



Illustrating R-4977

CATALOG NUMBER	GRATE TYPE	SQ. FT. OPEN	WEIR PERIMETER LINEAL FEET
R-4976-1	A or B	0.9	3.1
R-4976-2	A or B	1.5	4.2
R-4976-3	A or B	2.5	5.2
R-4976-4	A or B	3.7	6.3
R-4976-5	В	5.2	8.1
R-4977-1	A or B	1.5	4.0
R-4977-2	A or B	2.0	5.0
R-4977-3	A or B	3.7	10.0
R-4977-4	A or B	5.3	12.0
R-4977-5	A or B	8.0	15.0