





Z882-HDS

12 [305] WIDE REVEAL TRENCH DRAIN SYSTEM WITH STAINLESS STEEL FRAME

TAG _____

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES



Note: + Actual Channel length is 98 3/8 [2499] to allow for overlap.

ENGINEERING SPECIFICATION: Zurn Z882-HDS Channels shall be 96 [2438] long, 12 [305] wide reveal and have a 9-1/4 [235] throat. Modular channel sections shall be made of 0% water absorbent High Density Polyethylene (HDPE). Shall have a positive mechanical connection between channel sections that will not separate during the installation and shall mechanically lock into the concrete surround every 12 [305]. Channels shall weigh less than 5.05 lbs. [2.29kg] per linear foot, have a smooth, 3 [76] radiused self cleaning bottom with a Manning's coefficient of 0.009 and 1.04% or neutral 0% built in slope. Channels shall have all grates locked down. Shall have rebar clips standard to secure trench in its final location. Shall be provided with the standard RFS grates that lock down to the frame. Zurn 12 [305] wide reveal Stainless Steel Reinforced Slotted Grate conforming to ASTM specification A351, Grade CF8 (type 304), Fabricated grate is rated class B per the DIN EN1433 top load classification. Supplied in 24 [608] nominal lengths with 3/8 [10] wide slots, 1-1/2 [38] bearing depth. Grate has an open area of 25.61 sq. in. per ft [54207 sq. mm per meter]. Tie down recesses provided for securing option. The 1/4 [6] thick Stainless Steel Frame Assembly conforms to ASTM specification A-240 (type 304). with 10 - 4 [102] long concrete anchors per 96 [2438]. Grate lockdown bars are integral to the frame. All welds must be performed by a certified welder per ASTM standard AWS D1.6. Frames Shall be produced in the USA.

PREFIX OPTIONS (Check/specify appropriate options)

___ Z Eight-foot High Density Polyethylene (HDPE) Channel, Heavy-Duty Stainless Steel Frame with Anchor Studs.*

SUFFIX OPTIONS (Check/specify appropriate options)

Outlet Adapters Add/Each

___ -E1 Closed End Cap
 ___ -E4 4 [102] No-Hub End Outlet
 ___ -E6 6 [152] No-Hub End Outlet
 ___ -E8 8 [203] No-Hub End Outlet
 ___ -U4 4 [102] No-Hub Bottom Outlet
 ___ -U6 6 [152] No-Hub Bottom Outlet
 ___ -U8 8 [203] No-Hub Bottom Outlet

Grate Options (Load Classifications are per DIN EN1433)

___ -BDC Black Acid Resistant Epoxy Coated Ductile Grate - Class C
 ___ -BDE Black Acid Resistant Epoxy Coated Ductile Grate - Class E
 ___ -DC Ductile Iron Solid Cover - Class C
 ___ -DGC Ductile Iron Slotted Grate - Class C
 ___ -DGE Ductile Iron Slotted Grate - Class E
 ___ -DGF Ductile Iron Slotted Grate - Class F
 ___ -HPD Heel-Proof Ductile Slotted Grate - Class B
 ___ -HPDE Heel-Proof Ductile Slotted Grate - Class E

Miscellaneous Options

___ -JC Joint Connector
 ___ -SF Type 304 Stainless Steel Top Frame
 ___ -SW Sidewall Extensions - 11 [279] High
 ___ -SW2 Double Sidewall Extensions - 22 [559] High
 ___ -VP Vandal-Proof Lockdown

MADE in the U.S.A.

___ -ADA-USA Meets Americans with Disabilities Act Requirements - Class C
 ___ -DGC-USA Ductile Iron Slotted Grate - Class C
 ___ -DGE-USA Ductile Iron Slotted Grate - Class E
 ___ -FS Fabricated Stainless Steel Slotted Grate - Class A
 ___ -GG Fiberglass Grate - Class A
 ___ -PS Perforated Stainless Steel Grate - Class A
 ___ -RFS Reinforced Stainless Steel Slotted Grate - Class B *
 ___ -RPS Reinforced Stainless Steel Perforated Grate - Class B
 ___ -SBG-L Stainless Steel Bar Grate - Class B

Miscellaneous Options

___ -DB Bottom Dome Strainer

*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED

Trench No.	'A' Shallow Inv.	'B' Deep Inv.	Flow		
			(cfs)	(gpm)	(lps)
8201	6.25 [159]	7.25 [184]	1.241	557	35
8202	7.25 [184]	8.25 [210]	1.725	774	49
8203	8.25 [210]	9.25 [235]	2.226	999	63
8203N	9.25 [235]	9.25 [235]	-	-	-
8204	9.25 [235]	10.25 [260]	2.745	1232	78
8205	10.25 [260]	11.25 [286]	3.271	1468	93
8206	11.25 [286]	12.25 [311]	3.808	1709	108
8206N	12.25 [311]	12.25 [311]	-	-	-
8207	12.25 [311]	13.25 [337]	4.347	1951	123
8208	13.25 [337]	14.25 [362]	4.893	2196	139
8209	14.25 [362]	15.25 [387]	5.443	2443	155
8209N	15.25 [387]	15.25 [387]	-	-	-
8210	15.25 [387]	16.25 [413]	5.996	2691	170
8211	16.25 [413]	17.25 [438]	6.551	2940	186
8212	17.25 [438]	18.25 [464]	7.106	3189	202

REV. B DATE: 7/15/11 C.N. NO. 121596

DWG. NO. 301770 PRODUCT NO. Z882-HDS