



Z886-HDD

Supplied By: **TRENCH DRAIN SUPPLY**



877-903-7246
www.trenchdrainsupply.com

4.75 [121] WIDE REVEAL TRENCH DRAIN SYSTEM
WITH DOMESTIC DUCTILE IRON GRATE

TAG _____

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES



NOTE: + Actual Channel length is 81 1/4 [2064] to allow for overlap.

ENGINEERING SPECIFICATION: Zurn Z886-HDD Channels shall be 80 [2032] long, 4.75 [121] wide reveal and have a 4 [102] throat. Modular channel sections shall be made of 0% water absorbent High Density Polyethylene (HDPE). Shall have a positive mechanical connection between channel sections that will not separate during the installation and shall mechanically lock into the concrete surround a minimum of every 10 [254]. Channels shall weigh less than 2.31 lbs.[1.05kg] per linear foot, have a smooth, 1.5 [38] radiused self cleaning bottom with a Manning's coefficient of 0.009 and 0.75% or neutral 0% built in slope. Channels shall have rebar clips standard to secure trench in its final location. Shall be provided with standard HDD grates that lock into the concrete surround during installation and is intended for dynamic traffic loadings. Zurn 4.75 [121] wide reveal Highway Domestic Ductile Iron slotted grate conforming to ASTM specification A536-84, Grade 80-55-06. The un-coated ductile iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 20 [508] nominal lengths with 1.625 [41] wide slots, and 2.5 [64] bearing depth. Grate has an open area of 39.22 sq. in per ft. [83,016 sq. mm per meter]. System is Made in the USA.

PREFIX OPTIONS (Check/specify appropriate options)

___ Z Six-foot, Eight-inch High Density Polyethylene (HDPE)*

SUFFIX OPTIONS (Check/specify appropriate options)

Outlet Adapters Add/Each

- ___ -E1 Closed End Cap
- ___ -E2 2 [51] No-Hub End Outlet
- ___ -E3 3 [76] No-Hub End Outlet
- ___ -E4 4 [102] No-Hub End Outlet
- ___ -E6 6 [152] No-Hub End Outlet
- ___ -U2 2 [51] No-Hub Bottom Outlet
- ___ -U3 3 [76] No-Hub Bottom Outlet
- ___ -U4 4 [102] No-Hub Bottom Outlet
- ___ -U6 6 [152] No-Hub Bottom Outlet

Frame Options

- ___ -SW Sidewall Extensions - 9 [229] High
- ___ -SW2 Sidewall Extensions - 18 [457] High

Grate Options (Load Classifications are per DIN EN1433)

- ___ -GHDD Galvanized Highway Ductile Domestic Grate - Class C
- ___ -HR Ductile Iron Removable Grate/Frame System -H20/H25 - Class C

Miscellaneous Options

- ___ -JC Joint Connector

Trench No.	'A' Shallow Inv.	'B' Deep Inv.	Flow		
			(cfs)	(gpm)	(lps)
8601	5.22 [133]	5.82 [148]	0.21	93	6
8602	5.82 [133]	6.42 [163]	0.27	122	8
8603	6.42 [163]	7.02 [178]	0.34	152	10
8603N	7.02 [178]	7.02 [178]	-	-	-
8604	7.02 [178]	7.62 [194]	0.41	183	12
8605	7.62 [194]	8.22 [209]	0.48	214	13
8606	8.22 [209]	8.82 [224]	0.55	245	15
8606N	8.82 [224]	8.82 [224]	-	-	-
8607	8.82 [224]	9.42 [239]	0.62	276	17
8608	9.42 [239]	10.02 [255]	0.69	308	19
8609	10.02 [255]	10.62 [270]	0.76	339	21
8610	10.62 [270]	11.22 [285]	0.83	371	23
8611	11.22 [285]	11.82 [300]	0.90	403	25
8612	11.82 [300]	12.42 [315]	0.97	435	27
8612N	12.42 [315]	12.42 [315]	-	-	-
8613	12.42 [315]	13.02 [331]	1.04	467	29
8614	13.02 [331]	13.62 [346]	1.11	498	31
8615	13.62 [346]	14.22 [361]	1.18	530	33

*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED

REV. B DATE: 2/24/11 C.N. NO. 111584

DWG. NO. 94164 PRODUCT NO. Z886-HDD

ZURN INDUSTRIES, LLC ♦ SPECIFICATION DRAINAGE OPERATION ♦ 1801 Pittsburgh Ave. ♦ Erie, PA 16514

Phone: 814455-0921 ♦ Fax: 814454-7929 ♦ World Wide Web: www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905405-8272 Fax: 905405-1292