

## CPZ886 Complete Kit

Series

**CPZ886**

Cut Sheet

Zurn Z886 Series

### 6" Wide Reveal Zurn Z886 HDPE Trench Drain Kit

### Z886 Complete Kit



**A Class - FG Galvanized  
Slotted Grate Standard**

### New Zurn Z886 HDPE Trench Drain Complete Kit 6 Inch Wide - A Class Galvanized Grate Standard.

#### Complete system - Each Kit Includes:

- Specified Number of 80" Sections of Z886 Channel.
- Specified Number of 40" A Class Galvanized Slotted Grates Standard.
- 2 Solid End Caps - 1 Outlet End Cap.—1 Bottom Outlet
- Galvanized Lock Hardware for the Grates.

#### Z886 Features and Benefits:



- 80" Modular Channels with 20" and 40" Grates.
- .75% Built-In Slope. Handles Greater Flows, Uniform Slope.
- Radiused Bottom. Better Flow Rate, Less Debris Build-Up.
- Smooth High Density Polyethylene Structural Composite Interior.
- 0% Water Absorption. Durable and Lightweight.



|   |   |
|---|---|
| <b>Number</b><br><b>Z886 HDPE Channel</b> | <b>Series</b><br><b>CPZ886</b><br>HDPE Channel<br>Z886 Series |
|---|---|

Dimensional Data (inches and [ mm ]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES



NOTE: + Actual Channel length is 81 1/4 [2064] to allow for overlap.

**ENGINEERING SPECIFICATION:** Zurn Z886 Channels are 80" [2032mm] long, 6-1/4 [159] wide reveal and have a 4" [102mm] throat. Modular channel sections are made of 0% water absorbent High Density Polyethylene (HDPE). Channels have a positive mechanical connection between channel sections that will not separate during the installation and mechanically lock into the concrete surround a minimum of every 10" [254mm]. Channels weigh less than 2.31 lbs. per linear foot [3.9 kg/m], have a smooth, 1-1/2" [38mm] radiused self cleaning bottom with a Manning's coefficient of .009 and .75% or neutral 0% built in slope. Channels have rebar clips standard to secure trench in its final location. Channels are provided with standard DGC grates that lock down with lockdown bars to the channel and is not intended for dynamic traffic loadings. Zurn 5-3/8" [137mm] wide reveal Ductile Iron Slotted Grate conforming to ASTM specification A536-84, Grade 80-55-06. Ductile Iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 20" [508mm] nominal lengths with 1/2" [13mm] wide slots, and 3/4" [19mm] bearing depth. Grate has an open area of 28.1 sq. in per ft. [60,308 sq. mm per meter].




| Trench No. | 'A' Shallow Inv. | 'B' Deep Inv. | Flow  |       |       |
|------------|------------------|---------------|-------|-------|-------|
|            |                  |               | (cfs) | (gpm) | (lps) |
| 8601       | 3.50 [89]        | 4.10 [104]    | 0.21  | 93    | 6     |
| 8602       | 4.10 [104]       | 4.70 [119]    | 0.27  | 122   | 8     |
| 8603       | 4.70 [119]       | 5.30 [135]    | 0.34  | 152   | 10    |
| 8603N      | 5.30 [135]       | 5.30 [135]    | -     | -     | -     |
| 8604       | 5.30 [135]       | 5.90 [150]    | 0.41  | 183   | 12    |
| 8605       | 5.90 [150]       | 6.50 [165]    | 0.48  | 214   | 13    |
| 8606       | 6.50 [165]       | 7.10 [180]    | 0.55  | 245   | 15    |
| 8606N      | 7.10 [180]       | 7.10 [180]    | -     | -     | -     |
| 8607       | 7.10 [180]       | 7.70 [196]    | 0.62  | 276   | 17    |
| 8608       | 7.70 [196]       | 8.30 [211]    | 0.69  | 308   | 19    |
| 8609       | 8.30 [211]       | 8.90 [226]    | 0.76  | 339   | 21    |
| 8610       | 8.90 [226]       | 9.50 [241]    | 0.83  | 371   | 23    |
| 8611       | 9.50 [241]       | 10.10 [257]   | 0.90  | 403   | 25    |
| 8612       | 10.10 [257]      | 10.70 [272]   | 0.97  | 435   | 27    |
| 8612N      | 10.70 [272]      | 10.70 [272]   | -     | -     | -     |
| 8613       | 10.70 [272]      | 11.30 [287]   | 1.04  | 467   | 29    |
| 8614       | 11.30 [287]      | 11.90 [302]   | 1.11  | 498   | 31    |
| 8615       | 11.90 [302]      | 12.50 [318]   | 1.18  | 530   | 33    |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|   |   |
|---|---|
| <p><b>Number</b><br/><b>Z886 E1 Solid End Cap</b></p> | <p><b>Series</b><br/><b>CPZ886</b><br/>HDPE Endcaps<br/>Z886 Series</p> |
|---|---|



| Please Check<br>✓ | Item No. | Part Number | Item I.D. |
|-------------------|----------|-------------|-----------|
|                   | 1        | 59895-001   | P886-E1   |

**Manufacturer**




**ENGINEERING SPECIFICATION: ZURN Z886-E1**

Closed End for 6" [152mm] wide Trench Drainage System.  
Endcap is made of 1/4" [6mm] thick HDPE.

**\*\*Unit to be cut in field per channel depth.**

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|   |   |
|---|---|
| <b>Number</b><br><b>Z886 E4 4" Outlet End Cap</b> | <b>Series</b><br><b>CPZ886</b><br>HDPE Endcaps<br>Z886 Series |
|---|---|



| Please Check | Item No. | Part Number | Item I.D. |
|--------------|----------|-------------|-----------|
| ✓            | 4        | 59896-003   | P886-E4   |

**Manufacturer**






**ENGINEERING SPECIFICATION: ZURN Z886-E4**

4" [102mm] No-Hub End Outlet for 6" [152mm] Wide Trench Drainage System. Outlet is made of 1/4" [6mm] thick HDPE and is designed for No-Hub applications using an adapter (Supplied by other).

**\*\*Unit to be cut in field per channel depth.**

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|  |   |
|--|---|
| <p><b>Number</b><br/><b>Z886 U4 4" Bottom Outlet</b></p> | <p><b>Series</b><br/><b>CPZ886</b><br/>HDPE Endcaps<br/>Z886 Series</p> |
|--|---|



| Please Check<br>✓ | Item No. | Part Number | Item I.D. |
|-------------------|----------|-------------|-----------|
|                   | 7        | 59894-003   | P886-U4   |

**Manufacturer**



**ENGINEERING SPECIFICATION: ZURN Z886-U4**

4" [102mm] No-Hub Bottom Outlet for 6" [152mm] wide Trench Drainage System. Outlet is made of 3/16" [5mm] thick HDPE and is designed for No-Hub applications using an adapter (Supplied by other).

**\*\*Channel to be cut in field to inside diameter of outlet.**

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|   |   |
|---|---|
| <p><b>Number</b></p> <p><b>Z886 Accessories</b></p> | <p><b>Series</b></p> <p><b>CPZ886</b><br/>Accessories<br/>Z886 Series</p> |
|---|---|



**Z886-669558409**

Locks intended for use with DI and HPP grates



**Z886-669558499**

Locks intended for use Decorative SS grates



**Z886-669558879**

Locks intended for use with Galvanized grates



**Z886-669559539**

Locks intended for use with standard SS grates

**Z886-669558439**

Vandal Proof grate lockdowns Perma-GL-VP

**Additional Accessories**


| Part Number    | Description         | Intended Grates |
|----------------|---------------------|-----------------|
| Z886-669558419 | Overlap Connect Bag | DI and HPP      |
| Z886-669558429 | Rebar Clip Bag      | DI and HPP      |
| Z886-669558469 | Frame Parts Bag     | DI and HPP      |
| Z886-669558579 | End Cap Hardware    |                 |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|                                   |  |
|-----------------------------------|--|
| <b>Number</b><br><br><b>94472</b> | <b>Series</b><br><b>Z886-DGC-USA</b><br>C Class Slotted Ductile Iron Grate<br>P6-DGC-USA |
|-----------------------------------|--|



**Specification**

The Zurn P6-DGC-USA Slotted Grate, Ductile Iron Grate, is 5-3/8 inches wide by 20 inches long, weighing 4.5 lbs per linear foot. The grate has an open area of 28.1 square inches per linear foot, DIN Rating of C, ANSI Rating of Heavy-Duty, H-20 Load Rated. Supplied by Trench Drain Supply.




| <b>DGC-USA - Slotted Grate</b> |                           |
|--------------------------------|---------------------------|
| Material:                      | Ductile Iron              |
| DIN Rating:                    | Class C                   |
| Weight:                        | 4.5 lbs/ft.               |
| Open Area:                     | 28.1 in <sup>2</sup> /ft. |
| ANSI Rating:                   | Heavy-Duty                |
| Application:                   | Vehicle Traffic           |
| Slot Width/Hole Size:          | 1/2"                      |
| ADA:                           | No                        |
| H-20:                          | Yes                       |
| FAA:                           | No                        |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|                                   |  |
|-----------------------------------|--|
| <b>Number</b><br><br><b>64063</b> | <b>Series</b><br><br><b>Z886-FG</b><br>A Class Slotted Galvanized Steel Grate<br>P6-FG |
|-----------------------------------|--|



**Specification**

The Zurn P6-FG Fabricated Slotted, Galvanized Steel Grate, is 5-3/8 inches wide by 40 inches long, weighing 1.7 lbs per linear foot. The grate has an open area of 12.0 square inches per linear foot, DIN Rating of A, ANSI Rating of Light-Duty. Galvanizing conforms to ASTM specification A653, Galvanized Coating designation G60, minimum spangle. Supplied by Trench Drain Supply.




|                                |                           |
|--------------------------------|---------------------------|
| <b>FG - Fabricated Slotted</b> |                           |
| Material:                      | Galvanized Steel          |
| DIN Rating:                    | Class A                   |
| Weight:                        | 1.7 lbs/ft.               |
| Open Area:                     | 12.0 in <sup>2</sup> /ft. |
| ANSI Rating:                   | Light-Duty                |
| Application:                   | Pedestrian Traffic        |
| Slot Width/Hole Size:          | 3/8"                      |
| ADA:                           | No                        |
| H-20:                          | No                        |
| FAA:                           | No                        |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|                                   |   |
|-----------------------------------|---|
| <b>Number</b><br><br><b>58524</b> | <b>Series</b><br><br><b>Z886-HPD</b><br>B Class Heel-Proof Ductile Iron Grate<br>P6-HPD |
|-----------------------------------|---|



**Specification**

The Zurn P6-HPD Heel-Proof Slotted, Ductile Iron grate, is 5-3/8 inches wide by 20 inches long, weighing 6.3 lbs per linear foot. The grate has an open area of 17.0 square inches per linear foot, DIN Rating of B, ANSI Rating of Medium-Duty, ADA compliant. Supplied by Trench Drain Supply.


|                                 |                           |
|---------------------------------|---------------------------|
| <b>HPD - Heel-Proof Slotted</b> |                           |
| Material:                       | Ductile Iron              |
| DIN Rating:                     | Class B                   |
| Weight:                         | 6.3 lbs/ft.               |
| Open Area:                      | 17.0 in <sup>2</sup> /ft. |
| ANSI Rating:                    | Medium-Duty               |
| Application:                    | Heel-Proof                |
| Slot Width/Hole Size:           | 1/4"                      |
| ADA:                            | Yes                       |
| H-20:                           | No                        |
| FAA:                            | No                        |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|  |   |
|--|---|
| <p><b>Number</b></p> <p style="text-align: center;"><b>94001</b></p> | <p><b>Series</b></p> <p style="text-align: center;"><b>Z886-HPP</b></p> <p style="text-align: center;">A Class High Density Polyethylene Grate<br/>P6-HPP</p> |
|--|---|



**Specification**

The Zurn P6-HPP Heel-Proof Slotted, High Density Polyethylene (HDPE) grate, is 5-3/8 inches wide by 20 inches long, weighing .9 lbs per linear foot. The grate has an open area of 14.5 square inches per linear foot, DIN Rating of A, ANSI Rating of Light-Duty, ADA compliant. Supplied by Trench Drain Supply.


|                                 |                           |
|---------------------------------|---------------------------|
| <b>HPP - Heel-Proof Slotted</b> |                           |
| Material:                       | HDPE                      |
| DIN Rating:                     | Class A                   |
| Weight:                         | .9 lbs/ft.                |
| Open Area:                      | 14.5 in <sup>2</sup> /ft. |
| ANSI Rating:                    | Light-Duty                |
| Application:                    | Heel-Proof, Pedestrian    |
| Slot Width/Hole Size:           | 1/4"                      |
| ADA:                            | Yes                       |
| H-20:                           | No                        |
| FAA:                            | No                        |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|                                   |   |
|-----------------------------------|---|
| <b>Number</b><br><br><b>64078</b> | <b>Series</b><br><br><b>Z886-PG</b><br>A Class Perforated Galvanized Steel Grate<br>P6-PG |
|-----------------------------------|---|



**Specification**

The Zurn P6-PG Fabricated Perforated, Galvanized Steel Grate, is 5-3/8 inches wide by 40 inches long, weighing 1.6 lbs per linear foot. The grate has an open area of 5.3 square inches per linear foot, DIN Rating of A, ANSI Rating of Light Duty, ADA Compliant. Galvanizing conforms to ASTM specification A653, Galvanized Coating designation G60, minimum spangle. Supplied by Trench Drain Supply.




|                                   |                          |
|-----------------------------------|--------------------------|
| <b>PG - Fabricated Perforated</b> |                          |
| Material:                         | Galvanized Steel         |
| DIN Rating:                       | Class A                  |
| Weight:                           | 1.6 lbs/ft.              |
| Open Area:                        | 5.3 in <sup>2</sup> /ft. |
| ANSI Rating:                      | Light Duty               |
| Application:                      | Heel-Proof pedestrian    |
| Slot Width/Hole Size:             | 1/4"                     |
| ADA:                              | Yes                      |
| H-20:                             | No                       |
| FAA:                              | No                       |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|                                    |   |
|------------------------------------|---|
| <b>Number</b><br><br><b>301238</b> | <b>Series</b><br><br><b>Z886-PGR</b><br>A Class Perforated Galvanized Steel Grate<br>P6-PGR |
|------------------------------------|---|



**Specification**

The Zurn P6-PGR Fabricated Raised Perforated, Galvanized Steel Grate, is 5-3/8 inches wide by 40 inches long, weighing 1.8 lbs per linear foot. The grate has an open area of 5.3 square inches per linear foot, DIN Rating of A, ANSI Rating of Light Duty, ADA Compliant. Galvanizing conforms to ASTM Specification A653. Galvanized coating designation G60, minimum spangle. Supplied by Trench Drain Supply.




|                                     |     |
|-------------------------------------|-----|
| <b>PGR - Raised Perforated</b>      |     |
| Material: Galvanized Steel          |     |
| DIN Rating: Class A                 |     |
| Weight: 1.8 lbs/ft.                 |     |
| Open Area: 5.3 in <sup>2</sup> /ft. |     |
| ANSI Rating: Light Duty             |     |
| Application: Heel-Proof pedestrian  |     |
| Slot Width/Hole Size: 1/4"          |     |
| ADA:                                | Yes |
| H-20:                               | No  |
| FAA:                                | No  |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|                                    |   |
|------------------------------------|---|
| <b>Number</b><br><br><b>308430</b> | <b>Series</b><br><b>Z886-RFGC</b><br>C Class Reinforced Galvanized Steel Grate<br>P6-RFGC |
|------------------------------------|---|



**Specification**

The Zurn P6-RFGC Reinforced Slotted, Galvanized Steel Grate, is 5-3/8 inches wide by 40 inches long, weighing 4.8 lbs per linear foot. The grate has an open area of 12.0 square inches per linear foot, DIN Rating of C, ANSI Rating of Heavy-Duty. H-20 load rated. Galvanized Sheet conforms to ASTM specification A653, Galvanized Coating designation G60, minimum spangle. Hot Dip Galvanizing on Reinforcement conforms to ASTM Specification A123. Supplied by Trench Drain Supply.


|  |                           |
|--|---------------------------|
| <b>RFGC - Reinforced Slotted</b>                     |                           |
| Material: Galvanized Steel & Galvanized Ductile Iron |                           |
| DIN Rating:  | Class C                   |
| Weight:  | 4.8 lbs/ft.               |
| Open Area:   | 12.0 in <sup>2</sup> /ft. |
| ANSI Rating: Heavy-Duty                              |                           |
| Application: Roadway                                 |                           |
| Slot Width/Hole Size: 3/8"                           |                           |
| ADA:   | No                        |
| H-20:  | Yes                       |
| FAA:   | No                        |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

|   |  |
|---|--|
| <b>Number</b><br><br><p style="text-align: center;"><b>308342</b></p> | <b>Series</b><br><p style="text-align: center;"><b>Z886-RPGC</b><br/>C Class Reinforced Galvanized Steel Grate<br/>P6-RPGC</p> |
|---|--|



**Specification**

The Zurn P6-RPGC Reinforced Perforated, Galvanized Steel Grate, is 5-3/8 inches wide by 40 inches long, weighing 4.7 lbs per linear foot. The grate has an open area of 8.3 square inches per linear foot, DIN Rating of C, ANSI Rating of Heavy-Duty, ADA Compliant, H-20 Load Rated. Galvanized Sheet conforms to ASTM specification A653, Galvanized Coating designation G60, minimum spangle. Hot Dip Galvanizing on Reinforcement conforms to ASTM Specification A123. Supplied by Trench Drain Supply.

| <b>RPGC - Reinforced Perforated</b> |  |
|-------------------------------------|--|
| Material:                           | Galvanized Steel & Galvanized Ductile Iron |
| DIN Rating:                         | Class C                                    |
| Weight:                             | 4.7 lbs/ft.                                |
| Open Area:                          | 8.3 in <sup>2</sup> /ft.                   |
| ANSI Rating:                        | Heavy-Duty                                 |
| Application:                        | Roadway                                    |
| Slot Width/Hole Size:               | 5/16"                                      |
| ADA:                                | Yes  |
| H-20:                               | Yes  |
| FAA:                                | No   |

**Manufacturer**



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.